

---

A parallel space-time finite element method for the  
simulation of an electric motor

P. Gangl, M. Gobrial, O. Steinbach

---

**Berichte aus dem  
Institut für Angewandte Mathematik**



# Technische Universität Graz

---

A parallel space-time finite element method for the  
simulation of an electric motor

P. Gangl, M. Gobrial, O. Steinbach

---

**Berichte aus dem  
Institut für Angewandte Mathematik**

Bericht 2022/8

Technische Universität Graz  
Institut für Angewandte Mathematik  
Steyrergasse 30  
A 8010 Graz

**WWW:** <http://www.applied.math.tugraz.at>

© Alle Rechte vorbehalten. Nachdruck nur mit Genehmigung des Autors.

# A parallel space-time finite element method for the simulation of an electric motor

Peter Gangl, Mario Gobrial, Olaf Steinbach

## 1 Introduction

Shape and topology optimization of electrical machines [2] as well as the optimal control [4] subject to parabolic evolution equations require an efficient solution of the direct simulation problem which is forward in time, and in most cases also of the adjoint problem which is backward in time. Space-time discretization methods [8] are therefore a method of choice to solve the overall system at once, and also to allow for adaptive refinements and a parallel solution simultaneously in space and time. In the case of a fixed spatial domain the numerical analysis of a space-time finite element method was given, e.g., in [7], see also the review article [8] and the references given therein. In this note we present an extension of this approach in order to simulate an electric motor where one part, the rotor, is rotating in time, while the stator is fixed. In addition to the stator and the rotor we have to include an air domain which is non-conducting. Hence we have to deal with an elliptic-parabolic interface problem for the eddy current approximation of the Maxwell system in two space dimensions. In this paper we present its space-time finite element discretization and provide first numerical results using parallel solution strategies in order to handle the overall system in the space-time domain. More details on the numerical analysis of the proposed method and further numerical results will be given in our forthcoming paper [3].

This paper is structured as follows: In Section 2 we describe the mathematical model and its space-time variational formulation. Unique solvability is based on the Babuška–Nečas theorem, i.e., on injectivity and surjectivity of the operator which is

---

Peter Gangl  
Johann Radon Institute for Computational and Applied Mathematics,  
Altenberger Straße 69, 4040 Linz, Austria  
e-mail: peter.gangl@oeaw.ac.at

Mario Gobrial and Olaf Steinbach  
Institute of Applied Mathematics, TU Graz, Steyrergasse 30, 8010 Graz, Austria  
e-mail: gobrial@math.tugraz.at, o.steinbach@tugraz.at

associated to the bilinear form of the variational formulation. The space-time finite element discretization is given in Section 3, which also provides an a priori error estimate, i.e., Cea's lemma, for the numerical solution. Numerical results are given in Section 4, and finally we provide some conclusions and comment on ongoing work.

## 2 Mathematical model and space-time variational formulation

To model the electromagnetic fields in a rotating electric machine, we consider the eddy current approximation of the Maxwell equations,

$$\operatorname{curl}_y H(y, t) = j(y, t), \quad \operatorname{curl}_y E(y, t) = -\partial_t B(y, t), \quad \operatorname{div}_y B(y, t) = 0,$$

subject to the constitutive equations

$$B(y, t) = \mu(y)H(y, t) + M(y, t), \quad j(y, t) = j_i(y, t) + \sigma(y) \left[ E(y, t) + v(y, t) \times B(y, t) \right],$$

with the material dependent magnetic permeability  $\mu$ , the electric conductivity  $\sigma$ , and an impressed electric current  $j_i$ . Moreover,  $M$  is the magnetization which vanishes outside permanent magnets. For a reference point  $x \in \mathbb{R}^3$  we consider the trajectory  $y(t) = \varphi(t, x)$ , where the deformation  $\varphi$  is assumed to be bijective and sufficiently regular for all  $t \in (0, T)$ , satisfying  $\varphi(0, x) = x$ . Here,  $T > 0$  is a given time horizon. Finally, we introduce the velocity  $v(y, t) = \frac{d}{dt}y(t)$ . In addition we consider appropriate boundary and initial conditions to be specified.

When using the vector potential ansatz  $B(y, t) = \operatorname{curl}_y A(y, t)$ , and following the standard approach to consider a spatially two-dimensional reference domain  $\Omega \subset \mathbb{R}^2$  describing the cross section of the electric machine, this gives an evolution equation to find  $u(y, t)$  as third component of  $A = (0, 0, u)^\top$  such that

$$\sigma(y) \frac{d}{dt}u(y, t) - \operatorname{div}_y [v(y) \nabla_y u(y, t)] = j_i(y, t) - \operatorname{div}_y [v(y) M^\perp(y, t)] \quad (1)$$

is satisfied in the space-time domain

$$Q := \left\{ (y, t) \in \mathbb{R}^3 : y = \varphi(t, x) \in \Omega(t), \quad x \in \Omega \subset \mathbb{R}^2, \quad t \in (0, T) \right\}.$$

Note that in (1) we use the reluctivity  $\nu = 1/\mu$ , and the total time derivative

$$\frac{d}{dt}u(y, t) := \partial_t u(y, t) + v(y, t) \cdot \nabla_y u(y, t).$$

Moreover,  $M^\perp = (-M_2, M_1)^\top$  is the perpendicular of the first two components of the magnetization  $M$ . In addition to (1) we consider homogeneous Dirichlet boundary

conditions  $u = 0$  on  $\Sigma := \partial\Omega \times (0, T)$ , and the homogeneous initial condition  $u(x, 0) = 0$  whenever  $\sigma(x) > 0$  is satisfied for  $x \in \Omega$ .

The electric motor consists of a rotor in  $\Omega_r(t)$ , the stator in  $\Omega_s$ , and the air domain  $\Omega_{air}$  which is non-conducting, i.e.,  $\sigma = 0$  in  $\Omega_{air}$ . This shows that we can formulate (1) as an elliptic-parabolic interface problem. While the stator domain  $\Omega_s$  is fixed in time, i.e.,  $v \equiv 0$ , the rotating subdomain  $\Omega_r(t)$  can be described, when using polar coordinates, as

$$x = r \begin{pmatrix} \cos \varphi \\ \sin \varphi \end{pmatrix}, \quad y(t) = \varphi(t, x) = r \begin{pmatrix} \cos(\varphi + \alpha t) \\ \sin(\varphi + \alpha t) \end{pmatrix} \in \Omega_r(t), \quad t \in (0, T),$$

with  $\alpha > 0$  describing the velocity

$$v(y, t) = \frac{d}{dt} y(t) = \alpha r \begin{pmatrix} -\sin(\varphi + \alpha t) \\ \cos(\varphi + \alpha t) \end{pmatrix} = \alpha \begin{pmatrix} -y_2 \\ y_1 \end{pmatrix}.$$

The variational formulation of the parabolic-elliptic interface problem (1) is to find  $u \in X$  such that

$$\begin{aligned} b(u, z) &:= \int_0^T \int_{\Omega(t)} \left[ \sigma \frac{d}{dt} u z + \nu \nabla_y u \cdot \nabla_y z \right] dy dt \\ &= \int_0^T \int_{\Omega(t)} \left[ j_i z + \nu M^\perp \cdot \nabla_y z \right] dy dt \end{aligned} \quad (2)$$

is satisfied for all  $z \in Y$ , where  $Y := L^2(0, T; H_0^1(\Omega(t)))$  and

$$X := \left\{ u \in Y : \sigma \frac{d}{dt} u \in Y^*, u(x, 0) = 0 \text{ for } x \in \Omega : \sigma(x) > 0 \right\}.$$

Related norms are given by

$$\|z\|_Y^2 := \int_0^T \int_{\Omega(t)} \nu |\nabla_y z|^2 dy dt, \quad \|u\|_X^2 := \|u\|_Y^2 + \|w_u\|_Y^2,$$

where  $w_u \in Y$  is the unique solution of the variational formulation

$$\int_0^T \int_{\Omega(t)} \nu \nabla_y w_u \cdot \nabla_y z dy dt = \int_0^T \int_{\Omega(t)} \sigma \frac{d}{dt} u z dy dt \quad \text{for all } z \in Y. \quad (3)$$

The bilinear form  $b(\cdot, \cdot)$  as defined in (2) is bounded and satisfies an inf-sup stability condition, see [3, 7], i.e., for all  $u \in X$  and  $z \in Y$  there holds

$$|b(u, z)| \leq \sqrt{2} \|u\|_X \|z\|_Y, \quad \frac{1}{\sqrt{2}} \|u\|_X \leq \sup_{0 \neq z \in Y} \frac{b(u, z)}{\|z\|_Y}.$$

Moreover, the bilinear form  $b(\cdot, \cdot)$  is surjective, i.e., for any  $z \in Y$  there exists a  $u_z \in X$  such that  $b(u_z, z) > 0$  is satisfied, see [3]. Hence, all assumptions of the

Babuška–Nečas theorem [1, 5] are satisfied, i.e. we conclude unique solvability of the space-time variational formulation (2).

### 3 Space-time finite element discretization

For the space-time finite element discretization of the variational formulation (2) we introduce conforming finite dimensional spaces  $X_h \subset X$  and  $Y_h \subset Y$  where we assume as in the continuous case  $X_h \subset Y_h$ . For our specific purpose we even consider  $X_h = Y_h := S_h^1(Q_h) \cap X = \text{span}\{\varphi_k\}_{k=1}^M$  as the space of piecewise linear and continuous basis functions  $\varphi_k$  which are defined with respect to some admissible locally quasi-uniform decomposition  $\mathcal{T}_h = \{\tau_\ell\}_{\ell=1}^N$  of the space-time domain  $Q$  into shape-regular simplicial finite elements  $\tau_\ell$  of mesh size  $h_\ell$ , see, e.g., [6].

The Galerkin space-time finite element variational formulation of (2) reads to find  $u_h \in X_h$ , such that

$$b(u_h, z_h) = \int_0^T \int_{\Omega(t)} \left[ j_i z_h + v M^\perp \cdot \nabla_y z_h \right] dy dt \quad \text{for all } z_h \in Y_h. \quad (4)$$

Unique solvability of (4) is based on the discrete inf-sup stability condition

$$\frac{1}{\sqrt{2}} \|u_h\|_{X_h} \leq \sup_{0 \neq z_h \in Y_h} \frac{b(u_h, z_h)}{\|z_h\|_Y} \quad \text{for all } u_h \in X_h,$$

which follows as in the continuous case [3, 7], but makes use of the discrete norm

$$\|u_h\|_{X_h}^2 := \|u_h\|_Y^2 + \|w_{u_h, h}\|_Y^2 \leq \|u_h\|_Y^2 + \|w_{u_h}\|_Y^2 = \|u_h\|_X^2,$$

where  $w_{u_h, h} \in Y_h$  is the unique solution of the variational formulation

$$\langle v \nabla_y w_{u_h, h}, \nabla_y z_h \rangle_{L^2(Q)} = \langle \sigma \frac{d}{dt} u_h, z_h \rangle_Q \quad \text{for all } z_h \in Y_h. \quad (5)$$


As in [7] we can then derive Cea's lemma,

$$\|u - u_h\|_{X_h} \leq 3 \inf_{z_h \in X_h} \|u - z_h\|_X,$$

from which we conclude optimal order of convergence when assuming sufficient regularity for the solution. In particular we obtain linear convergence in the space-time mesh size  $h$  when assuming  $u \in H^2(Q)$ , see [3, 7].


## 4 Numerical results

As numerical example we consider an electric motor, where both the rotor and the stator are made of iron, with 16 magnets and 48 coils, see Fig. 1.



**Fig. 1** The unstructured mesh of the bottom of the motor, showing the different materials.

The motor is pulled up in time, where the rotation of the rotating parts, i.e., the rotor, the magnets and the air around the magnets, is already considered within the mesh for a 90 degree rotation. The time component is treated as the third spatial dimension with a time span  $(0, T)$ ,  $T = 0.015$  seconds. Moreover, 30 time slices are inserted in order to have a good temporal resolution, where the mesh is differently unstructured at every time  $t \in (0, T)$ , see Figure 2.




**Fig. 2** The full space-time cylinder of the motor for a 90 degree rotation with 333, 288 nodes and 1, 978, 689 elements. The time is treated as the third spatial component divided into 30 time slices. The rotating parts are already considered within the mesh.

The electric motor consists of isotropic materials, hence we choose the linear material parameters as given in Table 1.

**Table 1** Material parameters

material	$\sigma$	$\nu$
air	0	$10^7/(4\pi)$
coils	$5.8 \cdot 10^7$	$10^7/(4\pi)$
magnets	$10^6$	$10^7/(4\pi)$
iron	$10^7$	$10^7/(20400\pi)$

We solve the resulting linear system in parallel, using a mesh decomposition method provided by the finite element library Netgen/NGSolve<sup>1</sup>, see Fig. 3.



**Fig. 3** Space-time mesh decomposition into 5 subdomains.


We use MUMPS<sup>2</sup> supported by PETSc<sup>3</sup>, to solve the linear system. Figure 4 shows the time for solving the system in relation to the number of processors used for the parallel computation.

The solution of the Galerkin space-time finite element formulation (4) for the time span  $(0, T)$  with  $T = 0.015$  is not sufficient to visualize, since in this short time the solution is close to zero due to the zero initial condition. Instead, one may consider periodic conditions  $u(x, T) = u(x, 0)$  for  $x \in \Omega$ , see [3]. Here, we also present the results for the quasi-static problem using  $\sigma = 0$  for all material regions at any time, see Fig. 5 for the solution at different time slices. Note that this corresponds to the problem of magnetostatics which is widely used in practical applications together with time-stepping methods.


<sup>1</sup> <https://www.ngsolve.org>

<sup>2</sup> <http://mumps-solver.org>

<sup>3</sup> <https://petsc.org>



**Fig. 4** The computation times using the MUMPS solver and GMRES solver.



**Fig. 5** The solution of the static problem visualized on different time slices.

## 5 Conclusions

In this note we have described a space-time finite element discretization of an elliptic-parabolic interface problem to model an electric motor. The computed elec-

tromagnetic fields can be used to compute other characteristic quantities such as the torque and iron losses in order to optimize the shape and the topology of electric machines. Instead of initial conditions and a linear description of the involved materials one can easily include periodic conditions in time and a nonlinear material model. Although we have provided first results for a parallel solution of the resulting linear system of algebraic equations also using mesh decomposition algorithms, further work is required in the design of more efficient solution strategies using appropriate preconditioning and domain decomposition methods.

**Acknowledgments:** This work has been supported by the Austrian Science Fund (FWF) under the Grant Collaborative Research Center TRR361/F90: CREATOR Computational Electric Machine Laboratory. P. Gangl acknowledges the support of the FWF project P 32911. We would like to thank U. Iben, J. Fridrich, I. Kulchytska-Ruchka, O. Rain, D. Scharfenstein, and A. Sichau (Robert Bosch GmbH, Renningen, Germany) for the cooperation and fruitful discussions during this work.

## References

1. Babuška, I., Aziz, A.: Survey lectures on the mathematical foundation of the finite element method. In: *The Mathematical Foundations of the Finite Element Method with Applications to Partial Differential Equations*, pp. 1–359, Academic Press, New York (1972).
2. Gangl, P., Krenn, N.: Topology optimization of a rotating electric machine by the topological derivative. RICAM-Report 2022-31, Johann Radon Institute for Computational and Applied Mathematics, Linz, 2022
3. Gangl, P., Gobrial, M., Steinbach, O.: A space-time finite element method for the simulation of rotating electric machines. *Berichte aus dem Institut für Angewandte Mathematik, Bericht 2022/9*, TU Graz, 2022.
4. Langer, U., Steinbach, O., Tröltzsch, F., Yang, H.: Unstructured space-time finite element methods for optimal control of parabolic equations. *SIAM J. Sci. Comput.* **43** A744–A771 (2021).
5. Nečas, J.: Sur une méthode pour résoudre les équations aux dérivées partielles du type elliptique, voisine de la variationnelle. *Ann. Scuola Norm. Sup. Pisa* **16**, 305–326 (1962).
6. Neumüller, M., Karabelas, E.: Generating admissible space-time meshes for moving domains in (d+1) dimensions. In: Langer, U., Steinbach, O. (eds.) *Space-Time Methods. Applications to Partial Differential Equations*, Radon Series on Computational and Applied Mathematics, vol. 25, pp. 185–206. de Gruyter, Berlin (2019).
7. Steinbach, O.: Space-time finite element methods for parabolic problems. *Comput. Meth. Appl. Math.* **15**, 551–566 (2015).
8. Steinbach, O., Yang, H.: Space-time finite element methods for parabolic evolution equations: Discretization, a posteriori error estimation, adaptivity and solution. In: Langer, U., Steinbach, O. (eds.) *Space-Time Methods. Applications to Partial Differential Equations*, Radon Series on Computational and Applied Mathematics, vol. 25, pp. 207–248. de Gruyter, Berlin (2019).